

# Power Access

**Power Access** is an inset, flush mount unit. Bezel and door available in Versteel powder coat colors. Unit is factory installed in the work surface. Indicate specified location on your purchase order.

## SPECIFICATIONS

- Completely flush mounted in work surface
- Two (2) power outlets per unit
- One (1) Dual USB A+C charging port per unit
- Two (2) ports for data/AV jacks per unit
- 6" x 4" powder coated bezel
- Individually powered, soft-wired linking or hard-wired linking



## INDIVIDUALLY POWERED

- Standard plug for each unit
- Black cord available in three lengths: 36", 72" and 108"
- UL/CSA Listed

## SOFT-WIRED LINKING

- Single circuit, 15 amp
- No sequencing of units required
- Up to eight (8) units per circuit
- Requires BPS2 power supply per circuit
- Black cord available in three lengths: 72", 120", and 180"
- ETL Listed to the UL962 Standard

## HARD-WIRED LINKING

- Multi-circuit (4 wire, 2 circuit, 20 amp circuits)
- No sequencing of units required
- Up to 20 units per circuit
- UL/CSA Listed

## FINISHES + MATERIALS

- **Bezel and Door** Versteel standard and premium powder coats (excludes transparent powder coats)
- **Interior and Body** Black

## DATA/AV JACK OPTIONS

Data  
Voice  
HDMI  
Data Coupler  
Voice Coupler



**VERSTEEL**

**versteel.com**  
Made in America  
800 876 2120